

SBW-06D2X-U

Color

Black

Read Speed

BD-R : 6X

BD-RE : 6X

BD-ROM : 6X

BD-R(DL) : 6X

BD-RE(DL) : 6X

BD-ROM(DL) : 6X

BD-R(TL/QL) : 4X

BD-RE(TL) : 2X

DVD+R : 8X

DVD-R : 8X

DVD+RW : 8X

DVD-RW : 8X

DVD-ROM : 8X

DVD+R(DL) : 6X

DVD-R(DL) : 6X

DVD-ROM(DL) : 6X

DVD-RAM : 5X

CD-R : 24X

CD-RW : 24X

CD-ROM : 24X

BDMV Playback : 2X

DVD Video Playback : 4X

VCD Playback : 10X

Audio CD Playback : 10X

Write Speed

BD-R : 6X

BD-R(DL) : 6X

BD-R(TL/QL) : 4X

BD-RE : 2X

BD-RE(DL) : 2X

BD-RE(TL) : 2X

DVD+R : 8X

DVD-R : 8X
DVD+RW : 8X
DVD-RW : 6X
DVD+R(DL) : 6X
DVD-R (DL) : 6X
DVD-RAM : 5X
CD-R : 24X
CD-RW : 16X

Writing Mode

BD-RE : Random Write
BD-R : Sequential Write
DVD+R & DVD+R (DL) : Sequential Write
DVD-R & DVD-R(DL) : DAO/Incremental Recording
DVD+RW : Random Write
DVD-RW : DAO/Restricted Overwrite/Incremental Recording
DVD-RAM : Random Write
CD-R/RW : DAO/TAO/SAO/Packet Write

Access time

BD(SL/DL) : 300 ms
BD(TL/QL) : 450 ms
DVD : 190 ms
CD : 190 ms

Interface

USB 2.0

OS Support

Windows® 8
Windows® 7
Windows® Vista
Windows® XP
Windows® Server 2003
Windows® Server 2008
Mac OS X 10.6

System Requirements

CPU: Intel Pentium® D 945(3.4GHz) or higher
RAM: 1GB or more is recommended

Graphics Card: NVIDIA® GeForce 7600 GT or ATI X1600 series or above
Use HDCP Compatible display and VGA card to High Definition digital output

Software

Cyberlink Power2Go 8
TurboEngine

Disc Formats

Audio CD, Video CD, CD-I, CD-Extra, Photo CD, CD-Text, CD-ROM/XA, Multi-session CD, BD video, DVD Video

Disc Diameters

12cm/8cm

Dimensions

157 x 140 x 18.5 mm (LxWxH)

Weight

290 g
335 g (With Stand)

Power

USB Power +5V ± 5%

Temperature

Operating : 5 °C to 40 °C
Storage : -30 °C to 60 °C

Humidity

Operating : 15 % ~ 80 % (Non-condensing)
Storage : 10 % ~ 90 % (Non-condensing)
